

# BenchMix™

Programmable High Shear Lab Mixers

## Benefits for Your Lab:

- **Digital Display:**
  - ◆ Mixer Speed (RPM)
  - ◆ Tip Speed (Ft/Sec)
  - ◆ Pumping Rate (GPM)
  - ◆ Mixing Intensity (Bulk Velocity)
  - ◆ Elapsed time (Seconds)
- **Complete Scalability Techniques** from 1 Liter Lab Tests to 2000 Liter Production Units
- **Variable Speed** 1/2 Hp, 10,000 RPM Constant Torque PMDC Drive with Speed Regulation to 1% of Set Speed
- **Push Button Electric Lift** with Mechanical Brake and Clutch
- **Glass Beaded 316 SS Chassis** with NEMA 4X Overlay



*Advanced Mixing Technologies*



## Admix, Inc. introduces the first, fully programmable benchtop high shear lab mixer with built-in scale-up parameters.



The **BenchMix™ OPLB-300** takes the guesswork out of scaling from small to large volumes. Once satisfactory results are obtained with the **BenchMix** in any volume from 1 liter to 2 gallons of test material, the critical scaling parameters are indicated to proceed to much larger production size volumes.

### BenchMix OPLB-300 Specifications

<b>Mixing Head Types</b>	Rotosolver® Dispenser, Rotostat® Emulsifier or Low Speed Propellers in various sizes
<b>Output Speed</b>	500-10,000 RPM
<b>Horsepower</b>	1/2 HP maximum rating
<b>Motor Characteristics</b>	Permanent Magnet DC Brushless Drive with Hall Sensor for regulation to 1% of set speed
<b>Shaft Size</b>	10 mm x 356 mm (3/8" x 14")
<b>Mix Head Diameters</b>	29 mm (1.14") Rotosolver 50 mm (2") Rotostat with lower prop [XP] or without lower prop [X] (Optional) 1", 1½", 2" or 3" Propellers (Optional)
<b>Capacity</b>	1 to 12 Liters (1/4 to 3 Gallons)
<b>Weight</b>	55 lbs.
<b>Mixer Stand</b>	Glass Beaded 316SS Chassis with removable non-slip ribbed rubber mat
<b>Mixer Lift</b>	Push Button Electric Lift, 18" of travel in 27 seconds, mechanical brake and over running clutch. Sealed lift tube.
<b>Dimensions</b>	Overall Height: 27.2" - 45.2" Overall Depth: 19.25" Overall Width: 14.5"
<b>Controller / Display</b>	Closed Loop PLC / 115 Volt / 60 Hz System with digital, 2 line, 20 character alphanumeric display
<b>Output Profiles</b>	Ten (10) User Programmable Profiles, each with ten (10) Time, Speed, Delay, Prompt for User and End Steps. Pre-programmed for use with eight (8) separate mix heads.

234 Abby Road  
Manchester, NH 01303  
Tel: 603-627-2340

**1-800-466-2369**

Fax: 603-627-2019  
E-mail: [mixing@admix.com](mailto:mixing@admix.com)  
Web site: [www.admix.com](http://www.admix.com)



*Advanced Mixing Technologies*